



Quick Connect Pneumatic Fittings

Quick Coupling

Models Select Chart

Model	Description
A-3001-1	4 mm O.D. quick coupling x 1/8 male BSPT straight metal fitting.
A-3001-2	4 mm O.D. quick coupling x 1/4 male BSPT straight metal fitting.
A-3001-3	6 mm O.D. quick coupling x 1/8 male BSPT straight metal fitting.
A-3001-4	6 mm O.D. quick coupling x 1/4 male BSPT straight metal fitting.
A-3001-5	8 mm O.D. quick coupling x 1/8 male BSPT straight metal fitting.
A-3001-6	8 mm O.D. quick coupling x 1/4 male BSPT straight metal fitting.
A-3021-1	1/4" O.D. quick coupling x 1/8" male NPT straight metal fitting.
A-3021-2	1/4" O.D. quick coupling x 1/4" male NPT straight metal fitting.
A-3021-3	5/16" O.D. quick coupling x 1/8" male NPT straight metal fitting.
A-3021-4	5/16" O.D. quick coupling x 1/4" male NPT straight metal fitting.
A-3021-5	3/8" O.D. quick coupling x 1/8" male NPT straight metal fitting.
A-3021-6	3/8" O.D. quick coupling x 1/4" male NPT straight metal fitting.

Specification:-	
Service	: Air (no other gases or liquids).
Pressure Limits	: -29.5" Hg to 150 psi (-750 mm Hg to 10.3 bar).
Temperature Limits	: 32 to 140°F (0 to 60°C).
Weight	: 0.4 to 0.7 oz (11 to 19 g).