



Static Pressure Tips & Accessories

Senses Static Pressure

Models Select Chart

Model	Description
A-301	Static pressure tip, for 1/4" metal tubing connection.
A-301-A	Static pressure tip, for 1/4" metal tubing connection with 6" insertion depth.
A-301-B	Static pressure tip, for 1/4" metal tubing connection with 8" insertion depth.
A-301-C	Static pressure tip, for 1/4" metal tubing connection with 12" insertion depth.
A-301-SS	Static pressure tip, for 1/4" metal tubing connection in stainless steel.
A-302	Static pressure tip, for 3/16" and 1/8" ID plastic or rubber tubing.
A-302-A	Static pressure tip, for 3/16" and 1/8" ID plastic or rubber tubing with 6" insertion depth.
A-302F-A	303 SS Static pressure tip with mounting flange, for 3/16" I.D. rubber or plastic tubing. 4" insertion depth, includes mounting screws
A-302F-B	303 SS Static pressure tip with mounting flange, for 3/16" rubber or plastic tubing. 6" insertion depth, includes mounting screws
A-302F-C	303 SS Static pressure tip with mounting flange, for 3/16" rubber or plastic tubing. 8" insertion depth, includes mounting screws

A-303	Portable static pressure tip, for 3/16" ID rubber or plastic tubing with 4" insertion.
A-305	Static pressure tip, low resistance application, furnished with two (2) hex jam nuts and two (2) mounting washers for duct mounting and with 1/8" NPT pipe thread for pressure connection.
A-305-SS	Static pressure tip, low resistance application, furnished with two (2) hex jam nuts and two (2) mounting washers for duct mounting and with 1/8" NPT pipe thread for pressure connection in stainless steel.
A-306	Outdoor static pressure sensor, includes 50' vinyl tubing, mounting bracket and hardware. Red sensor.
A-306-A	Outdoor static pressure sensor, includes 50' vinyl tubing, mounting bracket and hardware. Gray sensor.
A-307	Static pressure fitting, for 1/4" metal tubing connection.
A-307-SS	Static pressure fitting, for 1/4" metal tubing connection in stainless steel.
A-308	Static pressure fitting, for 3/16" and 1/8" ID plastic or rubber tubing.
A-345	Flange for mounting A-301, A-302, A-307, A-308 or 1/8" dia Pitot tubes with compression fitting when interior of duct is not accessible. Aluminum material. With gasket and sheet metal screws.
A-414	316 SS clean room pressure sensor.
A-417A	Static pressure pickup. For use in clean rooms, 60 micron filter picks up static pressure. Stainless steel wall plate fits 2" x 4" electrical box. Sealed with foam gasket, screws included. Barbed brass fitting holds 1/8" to 3/16" ID tubing.
A-418A	Static Pressure Pickup. Room mount with Delta Style plastic enclosure fits 2" x 4" electrical box. Fine mesh screen hides static pressure pickup port. Clean connection to 1/8" to 3/16" I.D. tubing and pressure sensor. Sealed with foam gasket, screws included.
A-418E	Static Pressure Pickup, European housing. Room mount with plastic enclosure fits 2" x 4" electrical box. Fine mesh screen hides static pressure pickup port. Clean connection to 1/8" to 3/16" ID tubing and pressure sensor. Sealed with foam gasket, screws included.
A-418N	Static Pressure Pickup, North American housing. Room

	mount with plastic enclosure fits 2" x 4" electrical box. Fine mesh screen hides static pressure pickup port. Clean connection to 1/8" to 3/16" ID tubing and pressure sensor. Sealed with foam gasket, screws included.
A-419A	Static pressure pickup ceiling mount. Plate rests on top of standard 3/4" thick ceiling tile while 60 micron filter faces down through 5/8" hole in tile. Filter is barely noticeable in room being monitored. Unit mounts to junction box. Barbed brass fitting holds 1/8" to 3/16" ID tubing.
A-420A	Static pressure pickup for roof or outside mount. Reduces effects of wind gusts to keep pressure readings stable when plate is parallel to ground. Structure withstands harsh environmental elements. Structure is 3-1/4" across and 2-3/8" deep. EMT Conduit fitting is 1/2". Pressure connection is brass barbed fitting for 1/8" and 3/16" ID tubing.
A-421	Static pressure tip measures duct static air pressure, assembly includes 6" probe, silicon rubber hose and screws, built-in surge damper ensures stable readings, pressure spike reducer can be added to further smooth over pressure fluctuations.
A-465	Flush mount space pressure sensor
A-480	Plastic static pressure tip.
A-481	Installer kit, (includes 2 static pressure tips and PVC tubing).
A-489	4" 303 SS straight static pressure tip with flange.
A-491	6" straight SS static pressure tip with mounting flange.
A-493	8" straight SS static pressure tip with mounting flange.