



Metal Electronic Totalizing Meter
Batch or Cumulative Totals, Easy-to-Read LCD Display

Models Select Chart

EXAMPLE	TTMS	3	R	N	CE	TTMS-3RN-CE, TTMS Electronic Totalizing Meter, 1" Pipe Size, Stainless Steel, NPT Fitting, CE Approved
PIPE SIZE		1 2 3 4 5				1/2" 3/4" 1" 1-1/2" 2"
MATERIAL			R			Stainless Steel
FITTING TYPE				I N S		ISO (Female) NPT (Female) Sanitary Fitting
APPROVAL					CE	CE Approval

Specifications:-

Service	:	Compatible fluids.
Flow Range	:	1/2": 1 to 10 gpm (3.8 to 37.9 lpm); 3/4": 2 to 20 gpm (7.6 to 75.7 lpm); 1": 5 to 50 gpm (18.9 to 190 lpm); 1-1/2": 10 to 100 gpm (38 to 380 lpm); 2": 20 to 200 gpm (76 to 760 lpm).
Wetted Materials	:	Bearings: Ceramic; Shaft: Tungsten carbide; Rotor: PVDF; Rings: 316 SS; Body: SS.
Accuracy	:	±2.0% of reading
Repeatability	:	±0.1%
Batch Total Maximum	:	999,999.
Cumulative Total Maximum	:	99,999,900.
Temperature Limits	:	Computer: 0 to 140°F (-18 to 60°C); No computer: -40 to 250°F (-40 to 121°C)
Pressure Limits	:	NPT: 1500 psig (102 bar); Sanitary fitting: 100

		psig (6.9 bar).
Display	:	6-digit LCD, 3/4" H.
Connections: ISO, NPT or sanitary fitting options	:	ISO, NPT or sanitary fitting options.
Power Requirements	:	(2) 3V lithium, installed functional, user replaceable.
Battery Life	:	5 years.
Weight	:	1/2": 2.36 lb (1.07 kg); 3/4": 2.74 lb (1.24 kg); 1": 4.00 lb (1.81 kg); 1-1/2": 4.76 lb (2.16 kg); 2": 6.52 lb (2.96 kg).
Agency Approvals	:	CE.