



## Vane Flow Switch

Low Cost, Field Adjustable Set Point and Paddle

## Models Select Chart

Model	Description
FS-2	Paddle flow switch, 1" male NPT.
FS-2-BSPT	Paddle flow switch, 1" male BSPT.
FS-2-CND	Paddle flow switch, NPT process connection, conduit electrical connection
FS-2-W8	Paddle flow switch, 1" male NPT connection with 8 ft leads

## Accessories

Model	Description
FS-2-VANE	Replacement vane assembly

<b>Specifications:-</b>	
<b>Service</b>	: Compatible liquids.
<b>Wetted Materials</b>	: Bellow: Tin-bronze; Vane: SS; Body: Forged brass.
<b>Temperature Limits</b>	: 230°F (110°C).
<b>Pressure Limits</b>	: 145 psig (10 bar).
<b>Enclosure Rating</b>	: NEMA 4 (IP64).
<b>Switch Type</b>	: SPDT snap switch.
<b>Electrical Rating</b>	: 10 A res, 3 A ind @ 250 VAC.
<b>Electrical Connections</b>	: Cable gland with attached wire leads or optional conduit connection.
<b>Process Connection</b>	: 1" male NPT or BSPT.
<b>Mounting Orientation</b>	: Switch must be installed vertically on horizontal pipe runs.
<b>Set Point Adjustment</b>	: Four vane combinations and an adjustment screw.
<b>Enclosure</b>	: Die-cast aluminum alloy.
<b>Weight</b>	: 28.22 oz (0.8 kg).
<b>Agency Approvals</b>	: CE.

