



2.5" Industrial Pressure Gage

1.5% FS Accuracy, 316 SS or Brass Wetted Parts, Dual PSI/Bar x100 kPa Scales

MODELS SELECT CHART			
Model	Range	Model	Range
SGZ-D10122N	30" Hg to 0	SGY-D10122N	30" Hg to 0
SGZ-D10322N	0 to 30 psi	SGY-D10322N	0 to 30 psi
SGZ-D10422N	0 to 60 psi	SGY-D10422N	0 to 60 psi
SGZ-D10522N	0 to 100 psi	SGY-D10522N	0 to 100 psi
SGZ-D10622N	0 to 160 psi	SGY-D10622N	0 to 160 psi
SGZ-D10722N	0 to 200 psi	SGY-D10722N	0 to 200 psi
SGZ-D11022N	0 to 300 psi	SGY-D11022N	0 to 300 psi
SGZ-D11122N	0 to 500 psi	SGY-D11122N	0 to 500 psi
SGZ-D11222N	0 to 1000 psi	SGY-D11222N	0 to 1000 psi

Note: To order with glycerin fill add -GF to the end of the model.
For back connect, change 22N to 42N.

ACCESSORIES	
Model	Description
A-445D	U-bracket mounting kit for 2.5" gage
A-499R	Red sliding color pointer
A-499Y	Yellow sliding color pointer
A-499G	Green sliding color pointer

Specifications:-	
Service	: Compatible gases and liquids.
Wetted Materials	: SGZ: 316 L SS Tube, 316 SS connector; SGY: Brass connection, bronze tube.
Housing	: 304 SS.
Lens	: Polycarbonate.
Accuracy	: $\pm 1.5\%$ FS.
Pressure Limit	: FS range.
Temperature Limits	: -4 to 140°F (-20 to 60°C).
Size	: 2.5" (63 mm).
Process Connections	: 1/4" male NPT.
Weight	: 4.9 oz (141 g) bottom, 5.8 oz (164 g) back. Add 3.7 oz (104 g) for glycerin fill.

