



2.5" Low Pressure Gage

1.5% Full Scale Accuracy in a 2.5" Gage

| MODELS SELECT CHART | | | |
|---------------------|----------------------------------|-------------|--|
| Model | Range | Model | Range |
| LPG4-D7122N | -10 to 0 in w.c. (-2.5 to 0 kPa) | LPG4-D8322N | 0 to 40 in w.c. (0 to 10 kPa) |
| LPG4-D7222N | -15 to 0 in w.c. (-4 to 0 kPa) | LPG4-D8422N | 0 to 60 in w.c. (0 to 15 kPa) |
| LPG4-D7322N | -25 to 0 in w.c. (-6 to 0 kPa) | LPG4-D8522N | 0 to 80 in w.c. (0 to 20 kPa) |
| LPG4-D7422N | -40 to 0 in w.c. (-10 to 0 kPa) | LPG4-D8622N | 0 to 100 in w.c. (0 to 25 kPa) |
| LPG4-D7522N | -60 to 0 in w.c. (-15 to 0 kPa) | LPG4-D8722N | 0 to 160 in w.c. (0 to 40 kPa) |
| LPG4-D7622N | -80 to 0 in w.c. (-20 to 0 kPa) | LPG4-D8922N | -4 to 0 to 6 in w.c. (-1 to 0 to 1.5 kPa) |
| LPG4-D7722N | -100 to 0 in w.c. (-25 to 0 kPa) | LPG4-D9022N | -6 to 0 to 10 in w.c. (-1.5 to 0 to 2.5 kPa) |
| LPG4-D7822N | -160 to 0 in w.c. (-40 to 0 kPa) | LPG4-D9122N | -8 to 0 to 16 in w.c. (-2 to 0 to 4 kPa) |
| LPG4-D7922N | -235 to 0 in w.c. (-60 to 0 kPa) | LPG4-D9222N | -16 to 0 to 24 in w.c. (-4 to 0 to 6 kPa) |
| LPG4-D8022N | 0 to 10 in w.c. (0 to 2.5 kPa) | LPG4-D9322N | -24 to 0 to 40 in w.c. (-6 to 0 to 10 kPa) |
| LPG4-D8122N | 0 to 15 in w.c. (0 to 3.75 kPa) | LPG4-D9422N | -30 to 0 to 50 in w.c. (-7.5 to 0 to 12.5 kPa) |
| LPG4-D8222N | 0 to 25 in w.c. (0 to 6 kPa) | LPG4-D9522N | -40 to 0 to 60 in w.c. (-10 to 0 to 15.0 kPa) |

| Specifications:- | |
|----------------------------|---|
| Service | : Compatible gases and liquids. |
| Wetted Materials | : Brass and beryllium copper. |
| Housing | : Drawn steel, black finish. |
| Lens | : Polycarbonate (removable) |
| Accuracy | : $\pm 1.5\%$ FS. |
| Pressure Limit | : 100% of range scale. |
| Temperature Limits | : Process: -40 to 160 ⁰ F (-40 to 70 ⁰ C); Ambient: -40 to 140 ⁰ F (-40 to 60 ⁰ C). |
| Size | : 2.5" (63 mm). |
| Process Connections | : 1/4" male NPT. |
| Enclosure Rating | : NEMA 3 (IP54) |
| Weight | : 7.3 oz (0.21 kg). |
| | |