



Subminiature Pressure Switch
Field Adjustable

Models Select Chart

EXAMPLE	A2	5	4	0	1	2	Series A2-54012 Subminiature Pressure Switch, range 2-25 psi, 1/4" npt male process connection, SPST normally open circuit, spade terminal
SERIES	A2						Subminiature Pressure Switch
RANGE		5 6 7					2-25 psi 20-100 psi 50-150 psi
PROCESS CONNECTION			4 8				1/4" npt male 1/8" npt male
CIRCUIT				0 1			SPST normally open SPST normally closed
ELECTRICAL TERMINATION					1 3		spade terminal flying leads

Specifications:-

Service	:	Compatible liquids and gases.
Wetted Materials	:	Polymide film and brass.
Temperature Limits	:	-40 to 250°F (-40 to 121°C).
Pressure Limits	:	500 psi (34 bar).
Enclosure Rating	:	IP68 (Submersible models only).
Repeatability	:	±5% of highest set point.
Switch Type	:	SPST, 100 VA, 42 V
Electrical Connection	:	1/4" (6.3 mm) spade terminals or flying leads.
Process Connection	:	1/8" male NPT.
Weight	:	0.14 lb (0.06 kg).
Deadband	:	1-2 psi (0.07-0.14 bar).
Agency Approval	:	CE.