



General Purpose RTD

Fiberglass Insulated Wire

Models Select Chart

Model	Description
122095-00	Rigid extension type J thermocouple, 12" length, plug terminal.
122095-01	General purpose type K thermocouple with #6 spade terminals.
122095-06	Flex hose extension type J thermocouple, 0° bend, #6 spade terminal.
122095-07	Rigid extension type J thermocouple, 18" length, open terminal.
122095-10	Rigid extension type J thermocouple, 18" length, plug terminal.
122095-15	Flex hose extension type J thermocouple, 0° bend, plug terminal.
122095-16	Flex hose extension type J thermocouple, 90° bend, #6 spade terminal.
122095-19	Stainless steel overbraid extension type J thermocouple, 0° bend, #6 spade terminal.
122095-22	Stainless steel overbraid extension type J thermocouple, 90° bend, #6 spade terminal.
122095-26	Bayonet mount type J thermocouple, 48" length, #6 spade terminal.
122095-75	Bayonet mount type J thermocouple, 36" length, #6 spade terminal.
122095-76	Bayonet mount type J thermocouple, 36" length, plug terminal.
122095-77	Bayonet mount type J thermocouple, 60" length, #6 spade terminal.
122095-78	Bayonet mount type J thermocouple, 60" length, plug terminal.
122095-79	Bayonet mount type J thermocouple, 36" length, #6 spade terminal.
122095-81	Bayonet mount type J thermocouple, 48" length, #6 spade terminal.
122095-82	Bayonet mount type J thermocouple, 60" length, #6 spade terminal.
122095-84	General purpose type J thermocouple with #6 spade terminals.
122095-96	Rigid extension type J thermocouple, 12" length, open terminal.

Accessories

Model	Description
A-TC-K100-FB	K type, 100' on spool, fiber glass insulation, 450°C, yellow outer sheath, 24 AWG, 0.20 SQMM
A-TC-K100-FEP	K type, 100' on spool, FEP insulation, 200°C, yellow outer sheath, 24 AWG, 0.20 SQMM
A-TC-K25-FB	K type, 25' on spool, fiber glass insulation, 450°C, yellow outer sheath, 24 AWG, 0.20 SQMM
A-TC-K25-FEP	K type, 25' on spool, FEP insulation, 200°C, yellow outer sheath, 24 AWG, 0.20 SQMM
A-TC-K50-FB	K type, 50' on spool, fiber glass insulation, 450°C, yellow outer sheath, 24 AWG, 0.20 SQMM
A-TC-K50-FEP	K type, 50' on spool, FEP insulation, 200°C, yellow outer sheath, 24 AWG, 0.20 SQMM
A-TC-J100-FB	J type, 100' on spool, fiber glass insulation, 450°C, black outer sheath, 24 AWG, 0.20 SQMM
A-TC-J100-FEP	J type, 100' on spool, FEP insulation, 200°C, black outer sheath, 24 AWG, 0.20 SQMM
A-TC-J25-FB	J type, 25' on spool, fiber glass insulation, 450°C, black outer sheath, 24 AWG, 0.20 SQMM
A-TC-J25-FEP	J type, 25' on spool, FEP insulation, 200°C, black outer sheath, 24 AWG, 0.20 SQMM
A-TC-J50-FB	J type, 50' on spool, fiber glass insulation, 450°C, black outer sheath, 24 AWG, 0.20 SQMM
A-TC-J50-FEP	J type, 50' on spool, FEP insulation, 200°C, black outer sheath, 24 AWG, 0.20 SQMM