



Pressure/Temperature Data Logger

1/4" NPT Fitting, Up to 5000 psia

Models Select Chart

Model	Description
DLP-A08	Pressure/temperature data logger, range 0-30 psia.
DLP-A10	Pressure/temperature data logger, range 0-100 psia.
DLP-A13	Pressure/temperature data logger, range 0-300 psia.
DLP-A14	Pressure/temperature data logger, range 0-500 psia.
DLP-A15	Pressure/temperature data logger, range 0-1000 psia.
DLP-A19	Pressure/temperature data logger, range 0-5000 psia.
DLP-G08	Pressure/temperature data logger, range 0-30 psig.
DLP-G10	Pressure/temperature data logger, range 0-100 psig.
DLP-G13	Pressure/temperature data logger, range 0-300 psig.
DLP-G14	Pressure/temperature data logger, range 0-500 psig.

Accessories

Model	Description
DL700	Software, manual and USB interface cable(6').
TL-2150	Replacement battery.

Specifications:-	
Range	: Temperature: -40 to 176°F (-40 to 80°C); Pressure: 0 to 30 psia(g), 0 to 100 psia(g), 0 to 300 psia(g), 0 to 500 psia(g), 0 to 1000 psia, and 0 to 5000 psia depending on the model.
Memory Size	: 16,383 readings per channel.
Accuracy	: Temperature: ±0.9°F (±0.5°C); Pressure: 2% FSR, 0.25% at 77°F (25°C) typical.
Resolution	: Temperature: 0.2°F (0.1°C); Pressure: 0.002 psia(g), 0.005 psia(g), 0.05 psia(g), 0.05 psia, and 0.2 psia depending on the model.
Sampling Method	: Stop on memory full.
Sampling Rate	: Selectable from 2 sec to 12 hrs.
Computer Requirements	: Windows® 95, Windows® 98, Windows® 2000, Windows® ME, Windows NT®, and Windows® XP operating system, one free USB port.
Power Requirements	: 3.6 V TL2150 lithium metal battery, installed functional, user replaceable.
Battery Life	: 1 yr (approx).
Interface	: USB port (interface cable required).
Material	: Stainless steel.
Weight	: 12 oz (340 g).
Agency Approvals	: CE