



Straight Stainless Steel Pitot Tubes
Straight Design, Accurate Positioning

Models Select Chart

Model	Description
160F	Straight stainless steel pitot tube, 18"
160F-24	Straight stainless steel pitot tube, 24"
160F-36	Straight stainless steel pitot tube, 36"
160F-48	Straight stainless steel pitot tube, 48"
160F-60	Straight stainless steel pitot tube, 60"
160F-KIT	Kit containing 160F, 160F-24, 160F-36, 160F-48, and FREE carrying case

Accessories

Model	Description
A-156	Flange mounting plate with 1/2" female NPT.
A-158	Split flange.
A-159	Mounting gland with 1/2" male NPT.
A-397	Rugged step drill, quickly provides true round holes in thin materials, no center punch needed to start, automatically de-burrs drilled hole, high speed steel, drills 3/16" through 1/2" holes in 1/16" increments.
A-160-CASE	Pitot tube carrying case.

Specifications:-

Material	:	304 SS.
Accuracy	:	±2% FS, 0 to 9000 FPM (45 M/s).
K-Factor	:	0.81.
Max. Temperature	:	1500°F (815°C).
Process Connections	:	1/4" OD.
Weight	:	4.3 oz (122 g).
Agency Approvals	:	Meets the technical requirements of EU Directive 2011/65/EU (RoHS II).